

## Blackhawk Omni Trucker Edge Antenna

## 698-960/1710-2170 MHz, 6dBi / 8dBi (BH-OM-202TB or W)


Futureproof your vehicle installations with this high grade, ruggedised Omni Trucker Edge antenna. This premium grade cellular antenna will satisfy 3G and 4G capabilities for all the major networks in Australia and can be used for commercial and industrial 3G and 4G applications.

The Blackhawk Omni Trucker Edge Antenna (1070mm) will provide the perfect solution for voice and data applications where high gain antennas are required while on the move. Combine with Cel-Fi applications to never be out of contact when away from home.

## **Features:**

- Option of white or black antenna
- Height 1070mm
- Ruggedised construction for extreme conditions
- Extra heavy duty spring stainless steel base ideal for bull bar mount
- Included is 4 metres of RG58 cable supplied with FME female connector
- No tuning necessary

BLACKHAWK OMNI TRUCKER EDGE	
ELECTRICAL SPECIFICATIONS	MECHANICAL SPECIFICATIONS
Freq Range 698-960/1710-2170MHz	Height 1070mm
Impedance 50 $\Omega$	Weight 1.40kg
VSWR ≤ 1.2	Operating Temperature -40°C- +70°C
Gain 6dBi/8dBi	Termination FME-Female
Max Input Power 50W	Material Glass / Steel
Vertical Beamwidth H 360° E22°/E46°	Antenna Colour Black or white
	Diameter of installing pole 32.5mm



Horizontal Pattern (698-960/1710-2170)

Vertical Pattern

(698-960/1710-2170)

Email: sales@powertec.com.au Website: www.powertec.com.au



ABN: 42 082 948 463

16/511 Olsen Avenue Southport QLD 4215 Australia

Telephone: +61 7 5577 0500

Telephone: 1300 769 378